




r			
	T 2 2 1	B	B 11:11
m pistor mbly det	2 1 bottom piston insert 27 x 2 3/4" class A x 1665 3 1 valve adaptor nipple 1" BPC x 50 4 1 bottom piston hook attachment BSS 38 x 100 5 1 ball valve 23mm seat moulded supplied part 6 1 hook attachment 6 round bar x 130 7 1 ball retainer rod2 dia. 6 round bar x 34 8 1 25mm ball standard part 9 1 bottom piston added weight 33 x 2 RST x 650		

£...}






=



Kluil ridid drive waf Piston external one way Sleeve value. sealed Same as Cylinder stiffer flexible drive nember therible or rigid drive pe or any pipe connecting two two cylinders. hose pipe A F14 5



This Page is Inserted by IFW Indexing and Scanning Operations and is not part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

□ BLACK BORDERS
□ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
□ FADED TEXT OR DRAWING
□ BLURRED OR ILLEGIBLE TEXT OR DRAWING
□ SKEWED/SLANTED IMAGES
□ COLOR OR BLACK AND WHITE PHOTOGRAPHS
□ GRAY SCALE DOCUMENTS
□ LINES OR MARKS ON ORIGINAL DOCUMENT
□ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY

IMAGES ARE BEST AVAILABLE COPY.

OTHER:

As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.